

ULTRA Thermo Reactive Sealer

CONCRETE, STONE & MASONRY SEALER


PRODUCT DATA SHEET

CONCRETE AND MASONRY SEALER



Sealing Commercial and Residential Structures

- Roads
- Driveways
- Parking Decks
- Sidewalks
- Patios
- Basements
- Masonry Product
- Pavers
- Block
- Clay brick
- Artificial Brick
- Natural Stone
- Artificial Stone
- Mortar
- Stucco
- Architectural Features
- Counter tops
- Mantels
- Pools/Ponds
- Fountains and Statues



RECOMMENDED USES:

For sealing residential and commercial structures such as driveways, parking decks, sidewalks, basements and garage floors. Masonry products such as pavers, block, clay brick, artificial brick, natural and artificial stone, mortar and stucco. Compatible with most glues and topical coatings. Aids in curing new concrete.

DIRECTIONS:

Always test porosity prior to application (especially on dark surfaces). Surface must be porous and free of loose dirt, oil, grease, mildew, paint and other coatings. Hot water power washing prior to application is highly recommended then rinse liberally. Surface should be dry. No mixing is required. Do not apply below 40° F or above 100° F. Apply with heavy nap roller or low pressure sprayer highly saturating area. TRS could create a slightly white wet surface sheen and reacts /absorb within 1 minute. Puddles should be immediately dispersed with a roller. Generally only one application is required. Curing new concrete apply TRS

Caution:

KEEP OUT OF REACH OF CHILDREN. Avoid getting in eyes. In case of eye contact flush with water for 15 minutes. If swallowed, DO NOT induce vomiting contact a physician immediately.

"For over 30 years Power Line has provided quality engineered and environmentally sound cleaning maintenance programs for companies nationwide."

1-800-624-8186

For Sales - Nationwide 8-5 M.S.T.

Manufactured By
POWER LINE U.S.A.

14717 Heritagecrest Way • Riverton, UT 84065

www.powerlineindustries.com